

PD-7x7 PIR+LUX recessed On/Off white IP20

REF. 89212122-230



BASIC INFORMATION

DESCRIPTION

Presence and luminosity detector for flush mounting PIR. The recommended installation height is 2.8 m, with a maximum height of 8 m. It has a detection angle of 360° and an opening angle of 100°. The tangential detection range is 7 x 7 m and the radial detection range is 5 x 5 m.

The luminosity regulation range is 10 - 1000 lux and the timing range is 30 s - 30 min. The detector configuration is done through potentiometers and remote control.

It features a TEACH mode of operation. Possibility of interconnection between master/master and master/slave sensors up to 10 detectors. The control output is On/Off, and the maximum switchable power is 2000 W.

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C. White finish, protection degree IP 20, and dimensions: 120 x 120 x 113 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL

PUSH BUTTON

Yes

ETIM CLASS

EC000133

COMPATIBILITY

Simon Sensor Pro

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP20

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053357200

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.31

PRODUCT NET WEIGHT

0.174

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053357200

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

165

PACKAGING WIDTH

100

PACKAGING LENGTH

145

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2392500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.31

PACKAGING NET WEIGHT

0.174

PACKAGING WEIGHT UNIT

KGM