

Complete kit with 2xUSB charger, 3 schuko socket outlets and plate for 2 RJ45 connectors white S400 Top

REF. 42523020-130



BASIC INFORMATION

DESCRIPTION

Simon offers a product designed for those work spaces that require all connections in the same place. In the series 400 we find this kit of desk top complete with 2 x USB charger, 3 sockets of SCHUKOS and a plate for 2 RJ45 connectors, white colour. This version for 5 elements measures 250 x 120 x 80 millimetres and has a manual elevation system that allows us to access to it a practical way and instant. A product of avant-garde made of metal with a white finish, the trim cover is made of painted steel of anodised aluminium profile with a very resistant to the knocks. Simon offers an extra security in the case of combustion improbable, its covers and fastenings prevent is spread the flame, as they are manufactured in self-extinguishing thermoplastic, a product created pair current of 16 A and a voltage of 250 volts.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 A

RAL

9016

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

IP RATING

IP30

NUMBER OF RJ45 WINDOWS

2

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

FORMAT

Schuko

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

NUMBER OF SOCKETS

3 sockets for standard current circuit

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

OPERATING TEMPERATURE RANGE (°C)

-5...+60

NUMBER OF USB CHARGERS

1

IK CLASSIFICATION

07

TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

VERSION

5 elements

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

SECURING POSSIBILITIES

Using clips included in the fastening brackets

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

INSTALLATION TYPE

Suitable for fixing to furniture.

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2014/30/UE EMC;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;EN 60950-1:2006;EN 60950-1:2006 A11:2009;EN 60950-1:2006 A1:2010;EN 60950-1:2006 A12:2011;EN 60950-1:2006 A2:2011*3;ETSI-EN 301489-34 V1.4.1;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053195956

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053195956

PACKAGING VOLUME

3562500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

300

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

125

PACKAGING NET WEIGHT

0.85

UNITARY PACKAGING GROSS WEIGHT

0.85

PACKAGING LENGTH

95

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.85