

Ofiblock Compact for 4 useful mechanisms with rear diecut in the penultimate position

REF. KFC104NL1/14



BASIC INFORMATION

DESCRIPTION

Anodized aluminum Ofiblock Compact profile designed to deliver maximum functionality in a compact size, enabling the convergence of power, voice, data, and multimedia solutions. With its minimal depth and broad range of accessories, it supports multiple installation options on raised floors, walls, furniture, metallic surfaces with magnets, or on DIN rails. Developed to adapt to the specific needs of each space, it allows you to equip it with your personalized configuration of K45 modules, offering a versatile and efficient solution. Supplied with two side covers for quick connectors (Wieland type), providing the Ofiblock Compact with both electrical cable input and output. It also features a rear knockout in the penultimate position for optimal routing of the voice, data, or multimedia cabling connected to the K45 module you decide to install, which will be electromagnetically protected and shielded thanks to the included protective tray. Self-extinguishing, halogen-free thermoplastic covers ensure room safety in the event of a fire.

FINISH

Black

COMPATIBILITY

Functions of the Simon K45 range and combinable with the Simon Electrical Wiring range.

ETIM CLASS

EC002759

MATERIAL

Metal,Plastic

REMARKS

Profile with higher compactness to enable convergence of power, voice, data and multimedia solutions with minimal depth

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125°C (according to standard IEC 60670)

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MONOBLOCK

No

RAL

7021

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C (according to standard IEC 60670)

INSTALLATION DIRECTION

Horizontal, Vertical

SECURING POSSIBILITIES

Its design allows it to be surface-mounted on the wall, on table-top furniture, under a desk, on a raised floor, a metal surface with magnet, or on a DIN rail using specific fastening accessories.

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053290484

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053290484

PACKAGING VOLUME

907500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

60

PACKAGING GROSS WEIGHT

0.278

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

55

PACKAGING NET WEIGHT

0.244

UNITARY PACKAGING GROSS
WEIGHT

0.244

PACKAGING LENGTH

275

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.244