Adjustable depth trap for 6 modules S to be installed in concrete graphite color Simon CIMA

REF. **SF670/14**



BASIC INFORMATION

FINISH
Graphite

MATERIAL
Various

COMPATIBILITY
With Simon Series S and Simon 25 / Simon K45 (via adapter) mechanisms

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
16

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1800kg

RAL
7021

RECESS DIMENSION (MM)
210 x 300 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

CAN BE INSTALLED IN TRAY
Plástica y metálica

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052772

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
7483280

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
2.292

PRODUCT NET WEIGHT
2.292

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052772

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
79

PACKAGING WIDTH
236

PACKAGING LENGTH
342

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
7483280

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
2.292

PACKAGING NET WEIGHT
2.292

PACKAGING WEIGHT UNIT
KGM