# Customisable kit with dual opening cover and brushes, 4 schuko socket outlets and 8 empty elements black S400 Indesk Duo

REF. **46602000-138**



# BASIC INFORMATION

## DESCRIPTION

Cover with two opening and brushes, four socket-outlets SCHUKOS and 8 elements are the features of the kit gaps in the table customizable in black colour of the series Simon 400 Indesk Duo. Product suitable to be flush mounted in furniture with an intensity of 16 A and a voltage of 250 V ~. It has a insulation resistance > 5 M? at 500 V and dielectric strength with no holes or contours with 2000 V at 50H during a minute. It is necessary to combine with the functions of the series Simon 400 Indesk Duo to complete your installation. Also, this kit has a connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm your structure is composed of enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free, components that prevent toxic and the flame spread in case of fire.

## FINISH

Black

## MATERIAL

Metal

## COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

## PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

## ETIM CLASS

EC002759

## REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

### NUMBER OF POSSIBLE ELEMENTS
8

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

### NOMINAL VOLTAGE (V~)
250 V~

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9005

### NUMBER OF REAR ENTRANCES
8

### RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
4 sockets for standard current circuit

### VERSION
12 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With brush

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### REMOVAL OF COMPONENTS

### NUMBER OF COVER OPENING POSITIONS
2

### EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

### TYPE OF FASTENING
By lateral tightening of claws provided with the enclosure. Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45° and 135°

### REMOVAL OF THE PLATE
Only with tool

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053197165

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
3.4

PRODUCT NET WEIGHT
3.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053197165

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
370

PACKAGING WIDTH
135

PACKAGING LENGTH
200

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
9990000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
3.4

PACKAGING WEIGHT UNIT
KGM