

Double-pole switch 16AX 250V~ with built-in pilot light and screw terminal connection system grey Simon 27 Play

REF. 27134-67



BASIC INFORMATION

DESCRIPTION

Of the Simon 27 Play series comes this single-pole switch is compatible with elements up to 16 Amps and 250 Volt voltage for 1 element and two modules. With quick terminal connection, which uses a rocker operation. The manufacturing material used in this product is based on metal components with halogen-free insulation and thermoplastic trim. This switch has several additional finishes and its finished in grey socket, this single-pole switch. This series Simon 27 Play and the range has the possibility of exchanging the rockers, modifying the whim of the user the appearance of any room. A revolutionary system, one more than the brand it makes the market. To keep it in perfect condition this product, it is important to remember that it should be cleaned with a soft and dry cloth, avoiding the use of abrasive cloths or cleaners that contain chlorine. Compatible with other Simon series.

FINISH

Grey

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 AX	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP20	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
CONSUMPTION INDICATOR (MA) 0.55 mA	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	VERSION Single
NUMBER OF POSSIBLE ELEMENTS 1 element	TYPE OF MECHANISM Pivoting	VOLTAGE (V~) 250 V~
INDICATOR FUNCTION Yes		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 11	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.05

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

0.604

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053071335

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

603720

UNITS CONTAINED PACKAGING

5

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

54

PACKAGING NET WEIGHT

0.25

UNITARY PACKAGING GROSS

WEIGHT

0.05

PACKAGING WIDTH

52

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

215

MECANISMOS SIMON 27, 28 Y 44

Mecanismos básicos / Basic switches



Interrupor unipolar / Single-pole switch
XX00101-XX



Pulsador / Push button switch
XX00150-XX



Interrupor bipolar / Double pole switch
XX00133-XX



Conmutador / 2-way switch
XX00201-XX



Conmutador cruce / Intermediate switch
XX00251-XX

Mecanismos con piloto / Pilot switches



Interrupor unipolar / Single-pole switch
XX00102-XX



Interrupor bipolar / Double pole switch
XX00134-XX



Conmutador / 2-way switch
XX00202-XX



Interrupor unipolar / Single-pole switch
XX00104-XX



Pulsador / Push button switch
XX00160-XX



Conmutador / 2-way switch
XX2700204-XX



Conmutador cruce / Intermediate switch
XX2700254-XX