

Mini beacon kits 830.30 CW

REF. 83030042-876



BASIC INFORMATION

DESCRIPTION

To obtain a lighting to achieve that any room us shine with light own, Simon puts at your fingertips the kit mini beacon 830.30 with 3 luminaires, suitable for courtesy lighting or decorative. With a tone of lighting cold CW and a colour temperature of 5800 K, the kit mini 830.30 beacon with translucent optics for its 3 luminaires LED category A has a service life of 25,000 hours at 25 ° C and a performance of 250 lm for CW, and total luminaire consumption of 4.9 W and compatibility with power Volt voltage of 230 V, 50-60 Hz. Includes control system, switching on ON-OFF, for greater functionality of the luminaire, you can reach a temperature range of -15 ° C and 40 °C. With a size of luminaire of 0.45 () x3 3.3 mm, it is designed for installation semi-recessed both floor and wall, and has an finishes in stainless steel for a minimalist style of the set.

BODY MATERIAL

Stainless steel

APPLICATION

Indoor courtesy lighting,Indoor decorative lighting

PACKAGING CONTENTS

3 Units + 1 power supply

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

250 lm/4,9W

IP RATING

IP20

ELECTRICAL CLASS

Type 2

OPTICS

Translucent

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

230 V~

L70 (°C)

25,000 h at 25 °C

POWER (W)

4.9 W

COLOR TEMPERATURE (K)

5800 K

COLOR TYPE

CW

POWER SUPPLY DIMENSIONS (MM)

42.2x40.2x22 mm

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

51 lm/W

SERVICE LIFE

25.000 h

CRI

72

LUMENS (LM)

250 lm

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Semi-flush mount (wall, floor)

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

2 years 25,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053094006

PACKAGING VOLUME
2.16

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
1

PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
50

PACKAGING GROSS WEIGHT
0

UNITARY PACKAGING GROSS
WEIGHT
0.364

PACKAGING WIDTH
180

PACKAGING NET WEIGHT
0.364

PRODUCT NET WEIGHT
0.364

PACKAGING LENGTH
240

PACKAGING WEIGHT UNIT
KGM