Customisable kit with dual opening cover, brush, 4x USB charger, 6 schuko socket outlets and 4 empty elements white S400 Indesk Duo

REF. **46623000-130**



BASIC INFORMATION

DESCRIPTION

Among the flush-mounted devices in the Simon 400 Indesk Duo series, the customizable kit integrated into the table stands out, featuring a cover with two openings and a brush, a charger with 4 x USB ports, six schuko socket bases for standard current circuits, and four empty elements for personalization in white. Insulation resistance of >5 MO at 500 V, a current of 16 A, Wieland® gst18i connector with three aerial male poles with a 22 cm patch cord, voltage of 250 V~ and dielectric strength without perforation or contouring of 2000 V at 50 Hz for 1 minute are other of its characteristics. Why is this kit so resistant and safe? Because of the painted steel casing, anodized aluminum profile, covers and fastenings made of self-extinguishing thermoplastic and halogen-free materials with which its structure has been manufactured, materials that guarantee no flame propagation in case of fire and low toxicity in case of smoke emission.

FINISH

White

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

IK CLASSIFICATION
07

INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
-5...+60

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9016

NUMBER OF REAR ENTRANCES
4

RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

NUMBER OF SOCKETS
6 sockets for standard current circuit

NUMBER OF USB CHARGERS
2

VERSION
12 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS
With brush

CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

NUMBER OF COVER OPENING POSITIONS
2

EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

REMOVAL OF THE FRAME
Only with tool

INSTALLATION TYPE
Suitable for recessed mount in furniture.

OPENING ORIENTATION
At 45º and 135º

SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053273692

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
3.4

PRODUCT NET WEIGHT
3.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053273692

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
130

PACKAGING WIDTH
215

PACKAGING LENGTH
345

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
9642750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
3.4

PACKAGING WEIGHT UNIT
KGM