

2-way switch 16AX 250V~ with fast terminal connection system champagne Simon 31

REF. 31211-34



BASIC INFORMATION

DESCRIPTION

2-way switch, 16 A / 250V in champagne finish and with quick terminal connection system. It is part of the control mechanisms of the Simon 31 series. It can withstand temperatures very varied (of -25 to + 50 degrees centigrade) and works in rocker mode. These 2-way switches of the Simon 31 series are available in three different finishes, to ensure a perfect appearance during the installation in any room, it is advisable to choose the frame in the same colour as the rocker selected. I.e., in this case, you should position, place the frame in champagne finish. Is the individual version, of two modules and a single element, has dimensions of 64 x 65 millimetres and does not include any type of engraving on the 2-way switch. To ensure greater security for its use, it is made of metal components with halogen-free thermoplastic insulation and the trim is made of metallised thermoplastic. The stripping of the wire that require is 11 millimetres and supports a cable section of 1.5 to 2.5 millimetres maximum.

FINISH

Champagne

PACKAGING CONTENTS

Mechanism with rocker

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC001590

REMARKS

Available in 3 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

16 AX

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP21

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush
mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.091

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053049198

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

3026595

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.91

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

83

PACKAGING NET WEIGHT

0.91

UNITARY PACKAGING GROSS

WEIGHT

0.091

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221