

Extension 0.5 metres for aluminium column with 2 sides oval Simon K45

REF. ALK72P05/8



BASIC INFORMATION

DESCRIPTION

Model of element for Pole for fastening to the floor reference ALK72P05 / 8, It is part of the range of products and components of the series Simon professional 500 Cima, suitable for different environments and installations work Professionals and domesticas. It is an extension, 0.5 Meters for pole for fastening to the floor of 2 sides oval Simon K45, with the maximum Guarantees of solidity and versatile for different systems for fastening. Manufactured in aluminium material, Available finishes in colour and tone metal. Measures 500 x 80 x 110 mm, suitable For elements of different kinds of surfaces and environments. Work professionals.

FINISH

Metal

COMPATIBILITY

Simon K45 functions

ETIM CLASS

EC000795

MATERIAL

Aluminium

PACKAGING CONTENTS

Column extension, front cover, connecting pins and screws

REMARKS

To ensure the robustness of the unit, it is only possible to combine one extension per column

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

AVAILABLE IN

2-sided (square and oval) and 4-sided

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50Hz during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 Ω

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Separation by means of the compartments of the extension itself to eliminate any possible electromagnetic interference and transmission errors between the electric cables and Voice, Data and Multimedia.

HEAT RESISTANCE (°C)

+650°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MΩ at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

VERSION

2-sided (Oval)

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using connecting pins

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Vertical

REGULATIONS

REGULATIONS

UNE-EN 50.085-2-4:2006

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436050549

PRODUCT NET WEIGHT

1.5

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

5832000

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436050549

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.5

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

90

PACKAGING NET WEIGHT

1.5

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

120

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

1.5

PACKAGING LENGTH

540