

POINT 56 Spotlight Mini Rail 3000 K Flood DALI Black

REF. 92061312-388



BASIC INFORMATION

BODY MATERIAL

Aluminium injection moulding

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic, Office, Retail, Hotel, Contract

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

COLOR TYPE

NW

IP RATING

IP20

DIRECTIONAL

Yes

LIGHTING EFFICIENCY (LM/W)

hasta 79 lm/W

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DRIVER INCLUDED

Yes

LUMENS (LM)

1020 lm

POWER SUPPLY (V~)

220/240 V~

ELECTRICAL CLASS

II

NUMBER OF LUMINAIRES

1

RAL

9005

ENERGY EFFICIENCY

A+

MACADAM STEPS

<3 Step MacAdam

COLOR TEMPERATURE (K)

3000 K

L70 (°C)

150000h at 25°C

OPTICS

Flood 31°

CONTROL

DALI

L90 (°C)

40000h at 25°C

POWER (W)

14 W

CHROMATICS CRI ICONS

CRI
90

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Rail

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547052448

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.58

PRODUCT NET WEIGHT

0.4

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8436547052448

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

83

PACKAGING WIDTH

180

PACKAGING LENGTH

298

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

4452120

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.44

PACKAGING NET WEIGHT

0.4

PACKAGING WEIGHT UNIT

KGM