

Downlight 706.21 Flush mount NW Flood 1-10V White

REF. 70621130-384



BASIC INFORMATION

DESCRIPTION

It is a downlight 1-10 V of the range 706.21 with neutral colour temperature and Flood optics, white colour, the article is suitable for flush mounting and is characterized by a light output 950 lm / 15 W. The downlights 706 provide lighting ambience and also accent lighting. In terms of lighting ambience, this can lead to corners, such as fitting rooms, reception of a set of a hotel or bathrooms. With respect to the accent lighting, it is used to highlight objects on shelves. This downlight is, therefore, very versatile and also complies with a decorative function. Its functional design and simple makes it perfect for all kinds of environments, although it is especially suitable for retail and offices. The article weight 0.3 kg and has a service life of up to 30,000 hours at the time of installation, it is best to do so in a place where the temperature does not exceed 40°C for optimum conservation.

APPLICATION

Ambient lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS/W

950 lm/15W

IP RATING

IP44

ELECTRICAL CLASS

Type 2

OPTICS

Flood

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

INTEGRATED POWER SUPPLY

No

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

POWER (W)

15 W

COLOR TEMPERATURE (K)

3900 K

COLOR TYPE

NW

POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

CONTROL

1-10 V

LIGHTING EFFICIENCY (LM/W)

64 lm/W

SERVICE LIFE

30.000 h

CRI

80

LUMENS (LM)

950 lm

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

180

INSTALLATION TYPE

Flush mount

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053122204

PACKAGING VOLUME

3.034

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

0.506

UNITARY PACKAGING GROSS WEIGHT

0.506

PACKAGING WIDTH

145

PACKAGING NET WEIGHT

0.506

PRODUCT NET WEIGHT

0.506

PACKAGING LENGTH

155

PACKAGING WEIGHT UNIT

KGM