

Modular Lighting 729 120X30 Low Glare 3000K

REF. 72951033-683



BASIC INFORMATION

MATERIAL

Aluminium

APPLICATION

Office

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

COLOR TYPE

WW

IP RATING

IP20

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

50

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053305102

UNITARY PACKAGING HEIGHT

35

UNITARY PACKAGING WIDTH

39

UNITARY PACKAGING LENGTH

122.2

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

166803

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2

PRODUCT NET WEIGHT

1.75

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053305102

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

0

PACKAGING WIDTH

0

PACKAGING LENGTH

0

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.75

PACKAGING WEIGHT UNIT

KGM