# Plaque aveugle latérale pour profilé aluminium Ofiblock Compact et Ofiblock Line, gris clair Simon K45

RÉF. **ACFC01/24**



## INFORMATION DE BASE

### DESCRIPTION

It is a side blind cover for Ofiblock Compact aluminium profiles and Ofiblock Line with light grey finish, included in the series Simon K45, this piece has measures of 54 x 54 x 3 mm and is manufactured in thermoplastic material of character self-extinguishing and halogen-free. This means that, in case of fire, ensure that the fire is not propagate and also the low toxicity having smoke. It is a material very safe, which is also resistant to high temperatures. There is the option of providing this side cover with machined parts depending on the needs of the client and always under order. The product, in addition, it complies with the current regulation. For maintenance, it is sufficient to use a soft and dry cloth and lightly scrub it with it, avoid abrasive cleaners containing chlorine, as they could damage the cover.

### FINITION

Gris clair

### MATÉRIAU

Plastique

### CONTENU DE L'EMBALLAGE

Plaque aveugle latéral

### REMARQUES

Peut être fourni avec des pièces usinées en fonction des besoins du client (sur demande).

## INFORMATION TECHNIQUE

### MARCHÉ DISPONIBLE
CE

### TEMPÉRATURE MAX PENDANT LES TRAVAUX DE CONSTRUCTION (°C)
+60° C

### RÉSISTANCE À LA CHALEUR (°C)
+125°C (selon la norme IEC 60670)

### RÉSISTANCE D'ISOLATION (V-MΩ)
>5 MOhm à 500 V

### CLASSIFICATION IP
IP4X

### DISPONIBILITÉ DU KIT
Oui

### CONNECTABLE
Non

### MAINTENANCE
Nettoyez avec un chiffon doux et sec. N'utilisez pas de chiffons abrasifs et/ou de nettoyants contenant du chlore.

### PLAGE DE TEMPÉRATURE PENDANT L'INSTALLATION (°C)
-5 à 60° C

### RAL
7035

## INSTALLATION ET MAINTENANCE

### RETRAIT DU COUVERCLE
Avec outil seulement

### EXTINCTION (°C)
+850°C (selon la norme IEC 60670)

## RÉGLEMENTATION

### RÉGLEMENTATIONS
Directive 2014/35/UE LVD + EN 60670-1:2005

## INFORMATION LOGISTIQUE

HAUTEUR EMBALLAGE UNITAIRE
0.00

LARGEUR EMBALLAGE UNITAIRE
0.00

LONGUEUR EMBALLAGE UNITAIRE
0.00

VOLUME EMBALLAGE UNITAIRE
0.30

UNITÉ DE VOLUME EMBALLAGE UNITAIRE
MMQ

POIDS BRUT EMBALLAGE UNITAIRE
0.01

POIDS NET DU PRODUIT
0.01

UNITÉ DE POIDS EMBALLAGE UNITAIRE
KGM

EAN EMBALLAGE
8426436039124

UNIT. CONTENUES EMBALLAGE
20

HAUTEUR EMBALLAGE
18.00

LARGEUR EMBALLAGE
27.00

LONGUEUR EMBALLAGE
20.00

UNITÉ DE MESURE EMBALLAGE
MMT

VOLUME EMBALLAGE
9720.00

UNITÉ DE VOLUME EMBALLAGE
MMQ

POIDS BRUT EMBALLAGE
3.20

POIDS NET EMBALLAGE
0.16

UNITÉ DE POIDS EMBALLAGE
KGM