

## Front kit for 1 element with 1 German socket outlet Simon iO gloss black Simon 100

REF. 10021108-138



## BASIC INFORMATION

### DESCRIPTION

Front kit designed to occupy 1 element has 1 Schuko Simon iO socket base. It is made from a neutral colour, a bright black and is part of the range of Simon 100 products, so it is compatible with the rest of elements of this range.

It is a type of product designed to be marketed in the EC and has dimensions of 85.5x83.5mm. The sense of installation that it allows is both horizontal and vertical.

To ensure proper maintenance and operation, a temperature range ranging from 5 to 40° C and in a storage temperature range of -25 to 50° C must be preserved. To clean this device it is necessary to use a cloth dampened with soapy water.

It is a device that works with a voltage: 250 V ~ and has a cut type of emborning (1 click). It occupies a single element and has been made based on regulations 2011/65 / UE RoHS + directive 2014/53 / UE RED + EN 50581: 2012 + ETSI-300-220-2 v2.4.1 + EN 60730-2- 7: 2015 + IEC 60884-1 Ed 3.2

### FINISH

Gloss black

### PACKAGING CONTENTS

Mechanism and instructions

### ETIM CLASS

EC000007

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### NUMBER OF POSSIBLE ELEMENTS

1 element

### INDICATOR FUNCTION

Yes

### CURRENT (A)

16 A

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TYPE OF MECHANISM

Insertion

### MONOBLOCK

No

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### VERSION

1 element

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Suitable for flush mounting

### KIT INSTALLATION DIRECTION

Vertical and horizontal

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + Directive 2014/53/UE RED + EN 50581:2012 + ETSI-300-220-2 v2.4.1 + EN 60730-2-7:2015 + IEC 60884-1 Ed 3.2

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053084113

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.058

### PRODUCT NET WEIGHT

0.058

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053084113

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

25.3

### PACKAGING WIDTH

84

### PACKAGING LENGTH

84

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

178516.8

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.058

### PACKAGING NET WEIGHT

0.058

### PACKAGING WEIGHT UNIT

KGM