

# Luminaire HOLE 25 Trimless 4000K Flood White CRI90

REF. 91420912-400



## BASIC INFORMATION

### FINISH

White

### APPLICATION

Trimless

### ETIM CLASS

EC001744

### MATERIAL

Aluminium

### PACKAGING CONTENTS

1 unit

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

98

### LUMENS (LM)

1540 lm

### IP RATING

IP44

### DRIVER INCLUDED

No

### LUMENS/W

1540

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### ELECTRICAL CLASS

Type 3

### MACADAM STEPS

<3 Step MacAdam

### POWER SUPPLY (V~)

11,3 V~

### L70 (°C)

150.000h at 25°C

### OPTICS

Flood 35°

### RAL

9016

### L90 (°C)

40.000h at 25°C

### POWER (W)

20 W

### COLOR TEMPERATURE (K)

4000 K

### LIGHTING EFFICIENCY (LM/W)

103 lm/W

### SERVICE LIFE

50.000 h

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Trimless

## REGULATIONS

### EAC MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

UNITARY EAN CODE

8436547078639

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547078639

PACKAGING VOLUME

807500

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

50

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

85

PACKAGING NET WEIGHT

0.14

UNITARY PACKAGING GROSS  
WEIGHT

0.26

PACKAGING LENGTH

190

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.14