Voice and data flat plate with dust cover for 1 element and 2 RJ45 connectors category 5e UTP black Simon K45

REF. **KB95U/14**



BASIC INFORMATION

DESCRIPTION

This plate of voice and data completely plate, it is part of the series Simon K45. This plate has a compact dust shutter and an element for two RJ45 category 5e UTP. The finish of the plate is stylish, thanks to its metallic material in black grey colour. Requires the use of cabling 22-26 AWG and measures 45x45 mm, with a depth of 30 mm This becomes a plate versatile, simple and functional, it is possible to install it recessed or on a surface-mounted. The manufacturing material is committed to the thermoplastic insulation, halogen-free. The security of the voice and data plate is much more, even at high temperatures. This is the individual version with the number of modules. The connection of the plate requires the use of a insertion tool and can be coupled one or two connectors to the same. Also, you can incorporate it to vertical enclosures, such as columns, Teleblock, channels, mechanism holder. To do this, you have to use the 90 ° positioner (ref. K66). This can be guide with security and ease the plate into a vertical position.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 5e UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-26 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e UTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
Yes

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Supplied with voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0.3

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.032

PRODUCT NET WEIGHT

0.032

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8426436042735

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

88

PACKAGING WIDTH

123

PACKAGING LENGTH

136

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

14720264

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.32

PACKAGING NET WEIGHT

0.32

PACKAGING WEIGHT UNIT

KGM