

Downlight 735.20 NW Extensive 1-10 V Black

REF. 73520138-784



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

2400 lm/22W

OPERATING TEMPERATURE RANGE (°C)

Max. temp.: 35°C

L70 (°C)

50,000 h

OPTICS

Extensive

COLOR TEMPERATURE (K)

4000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

1-10 V

COLOR TYPE

NW

POWER (W)

22 W

CRI

80

LIGHTING EFFICIENCY (LM/W)

109,1 lm/W

SERVICE LIFE

50.000 h

LUMENS (LM)

2400 lm

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053086421

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.5

PRODUCT NET WEIGHT

1.2

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053086421

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

285

PACKAGING LENGTH

255

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9811125

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

1.5

PACKAGING NET WEIGHT

1.2

PACKAGING WEIGHT UNIT

KGM