


Push-button switch with light symbol 10A 250V~ and fast terminal connection system aluminium Simon 31

REF. 31651-33



BASIC INFORMATION

DESCRIPTION

Push-button switch with aluminium finish, with light symbol and quick terminal connection system, belonging to the Simon 31 series. Has a rocker operation and is available in 5 different finishes; we recommend choosing a frame the same colour as the selected rocker. Made of metal components with halogen-free insulation and trim in metallised thermoplastic, its design follows regulations UNE-EN 60669-1:2002 + A1:2003 + A2:2009. It measures 64x65 mm and can be installed in places with a temperature of between 5 and 40°C, although it can also withstand extreme temperatures of -25 to 50°C, approximately. It supports a cable section of 1.5 to 2.5 mm with a stripped 11mm and to clean it, you will have to do it with a soft and dry cloth and never use abrasive cleaners containing chlorine, as the push-button switch could become damaged and start to function incorrectly.

FINISH

Aluminium

COMPATIBILITY

Simon 31 frames

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Available in 5 finishes. It is recommended to choose a frame the same colour as the selected rocker.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

VERSION

Single

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.078

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

3.027

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053071847

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING VOLUME

3026595

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.78

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

83

PACKAGING NET WEIGHT

0.78

UNITARY PACKAGING GROSS

WEIGHT

0.078

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221