

German double socket outlet 16A 250V~ with safety device and screw terminal connection system white Simon 500 Cima

REF. 50000472-030



BASIC INFORMATION

DESCRIPTION

The Simon 500 Cima series guarantees a optimum operation with the French socket outlet, in its double version, with the Schuko format, with a white finish, the mechanism includes a safety device. Its reference is 50000472-030. It can withstand a current of 16 A and a voltage of 250V~ The rocker operation is by screw and with a operation is by insertion. Suitable for installation in surface-mounted or flush-mounted in any universal box. The cross-cable section is between 1.5 and 2.5mm and the stripping of wire necessary of 12mm. It measures 100x50mm. It is manufactured with metallic components with self-extinguishing, halogen-free thermoplastic insulation. This material; guarantees no flame spread in case of fire in case of incentive and the low toxicity in case of smoke.

FINISH

White

PACKAGING CONTENTS

Double socket outlet with cover
and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

Possibility to order replacement cover in case of breakage, with article no.50001841-030

TECHNICAL INFORMATION

AVAILABLE MARKET CE	INSULATION RESISTANCE (V-MΩ) >5MΩ at 500V	TYPE OF MECHANISM Insertion
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	CURRENT (A) 16 A	NUMBER OF MODULES 2
NUMBER OF CONNECTIONS PER TERMINAL 2 connections per terminal	IP RATING IP20	MONOBLOCK No
DIELECTRIC STRENGTH No holes or contours, with 2000V at 50 Hz for 1 minute	LINKABLE Yes, using accessory 50000996-039	NOMINAL VOLTAGE (V~) 250 V~
FORMAT Schuko	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 9003
HEAT RESISTANCE (°C) +125°C (according rule IEC 60695-10-2)	TEMPERATURE RANGE DURING INSTALLATION (°C) -25 to 60 °C	NUMBER OF SOCKETS 2
INDICATOR FUNCTION No		VERSION Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 12	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Specific Simon 500 Cima	REMOVAL OF THE SOCKET Only with tool
REMOVAL OF COVER Only with tool	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw
EXTINGUISHING (°C) +850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)	INSTALLATION TYPE Suitable for surface and flush mounting	NUMBER OF TERMINALS 3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053254585

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.108

PRODUCT NET WEIGHT

0.108

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093153

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

112

PACKAGING WIDTH

117

PACKAGING LENGTH

269

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.525

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.08

PACKAGING WEIGHT UNIT

KGM

