

Wire outlet mechanism with 4 double terminals and fixing cable tie champagne Simon 31

REF. 31801-34



BASIC INFORMATION

DESCRIPTION

The cable outlet mechanism with 4 double terminals connection and fixing cable tie is part of the range Simon 31 and is a product essential to bring order and organization to any electrical panel. The mechanism of cable outlet is specially designed for wire to wire from 1.5 to 2.5 millimetres long, section 380 volts. It works by wire stripping of 7 millimetres and measures 64 x 65 millimetres. This mechanism output capes enables the use of 4 double terminals, making it multifunction. Without a doubt, it is a product necessary in any electrical panel, especially those that provide energy by a number of cables. Thanks to this mechanism of cable outlet, components and cables on a electrical panel will appear perfectly ordered and organized, which in the long presents great advantages. Between them, stands out the facilitation the maintenance of the electrical panel, its possible future expansion and, above all, the solution quick against possible problems. In addition, this product helps to plan the space from the beginning and its trim cover and beautiful champagne colour make it an element plus the design of the room or furniture where it is. Stand out its manufacturing materials that consist of metal components with halogen-free insulation.

FINISH

Champagne

PACKAGING CONTENTS

Wire outlet mechanism

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000011

REMARKS

For wire section up to 2.5 mm

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

POWER SUPPLY (V~)

380 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

NUMBER OF CONTACTS

4

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

NUMBER OF CONTROLLABLE CIRCUITS

2

NUMBER OF WIRES

4

NUMBER OF POSSIBLE ELEMENTS

1 element

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

7

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

UNE-EN 60998-1:2005

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053009239

PACKAGING VOLUME
3451140

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
10

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
83

PACKAGING GROSS WEIGHT
0.105

UNITARY PACKAGING GROSS
WEIGHT
0.011

PACKAGING WIDTH
165

PACKAGING NET WEIGHT
0.11

PRODUCT NET WEIGHT
0.011

PACKAGING LENGTH
252

PACKAGING WEIGHT UNIT
KGM