

Luminaire P2 15,1W 3000K with detector 8m HF+LUX and emergency IP54

REF. 89164000-153



BASIC INFORMATION

DESCRIPTION

Luminaire with integrated HF detector and emergency, power 15.1 W, luminous flux of 1674 and color temperature 3000 K. The duration of emergency mode is 3 hours according to the EN 60598-2-22 standard. The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°. The luminosity regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min. Allows for interconnection of master/master and master/slave luminaires. The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 40 °C. IP 54 and IK protection rating, white, and dimensions: Ø 320 x 120 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

IK CLASSIFICATION

03

MAXIMUM POWER (W)

400

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053402580

UNITARY PACKAGING GROSS WEIGHT

0.65

PACKAGING LENGTH

370

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.65

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053402580

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.204

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

370

PACKAGING NET WEIGHT

0.65

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM