Watertight luminaire 789 36W 4000K 1200

REF. **78937033-884**



BASIC INFORMATION

DESCRIPTION

Watertight luminaire for parking lot, garage, and technical area applications, designed to provide uniform and comfortable lighting in circulation areas. Linear design with high-uniformity opal diffuser for homogeneous light distribution, minimizing shadows and glare. Through-wired and double connector included, allowing for continuous runs of up to 10 luminaires per line. Installation type: Surface. Optics: 120. Color temperature: 4000K. Power: 36W. Lumens: 3600lm. Efficiency: 100lm/w. Protection degree IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 1265 mm x 65 mm x 65 mm.

APPLICATION

Parking,Industrial lighting,General lighting,Car park lighting

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
08

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-25...+40

POWER SUPPLY (V~)
220/240 V~

CONTROL
On/Off

LIGHTING EFFICIENCY (LM/W)
100 lm/W

LUMENS (LM)
3600 lm

OPTICS
General

POWER (W)
36 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440247

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.85

PRODUCT NET WEIGHT
0.76

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440247

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
225

PACKAGING WIDTH
300

PACKAGING LENGTH
1320

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
89100000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
10.2

PACKAGING NET WEIGHT
0.76

PACKAGING WEIGHT UNIT
KGM