Downlight 703.21 Round Comfort 2700 K Wide Flood DALI White

REF. **70321330-482**



BASIC INFORMATION

APPLICATION

Hotel,Restaurants,Residential,Retail,Office,Healthcare,Education

PACKAGING CONTENTS

1 Unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP44

OPERATING TEMPERATURE RANGE (ºC)
15 - 35 ºC

POWER SUPPLY (V~)
100/240 V~

COLOR TEMPERATURE (K)
2700 K

CONTROL
DALI

CRI
80

CUT OFF
No

DRIVER INCLUDED
Yes

L70 (ºC)
30,000 h at 25 °C

LIGHT BEAM APERTURE ANGLE (°)
40º

LIGHTING EFFICIENCY (LM/W)
91 lm/W

LUMENS (LM)
680 lm

LUMENS/W
680 lm/7.5 W

OPTICS
Wide Flood

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
7.5 W

SERVICE LIFE
30.000 h

CHROMATICS CRI ICONS



INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053088463

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.418

PRODUCT NET WEIGHT
0.295

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053088463

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.418

PACKAGING NET WEIGHT
0.295

PACKAGING WEIGHT UNIT
KGM