

2-way switch 10AX 250V~ with built-in pilot light and fast terminal connection system ivory Simon 27 Play

REF. 27202-62



BASIC INFORMATION

DESCRIPTION

This 2-way switch 10 AX 250V~ with built in light and offers quick terminal connection system. With ivory finish, this piece can be installed in the simplest way, thanks to this terminal connection system, as there is no need to strip cables. The article measures 45x45 mm and is made of socket of metal components with halogen-free insulation and trim in thermoplastic material in compliance with the regulation. It is characterized, also, by a high thermal resistance, so that you can adapt to all types of environments. The piece is part of the Simon 27 Play series and can be combined with the reference 2700802-037 in case of replacement of the indicator light, it is suitable for installation in surface and flush mounting and compatible with the frames of the series Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. To clean it, use a soft, dry cloth.

FINISH

Ivory

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC001590

REMARKS

Can be combined with article 2700802-037 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 10 AX	NOMINAL VOLTAGE (V~) 250 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 5 - 40 °C
CONSUMPTION INDICATOR (MA) 0.55 mA	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	STORAGE TEMPERATURE RANGE (°C) -25 - 50 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	TYPE OF MECHANISM Pivoting	VERSION Single
INDICATOR FUNCTION Yes		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 11	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal, American and Centralisations	INSTALLATION TYPE Suitable for surface and flush mounting
CLAW Simon 27	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.036

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING VOLUME

1229865

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053035955

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

1229865

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.355

UNITARY PACKAGING VOLUME
UNIT

MMQ

PACKAGING HEIGHT

53

PACKAGING NET WEIGHT

0.36

UNITARY PACKAGING GROSS
WEIGHT

0.036

PACKAGING WIDTH

105

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221

MECANISMOS SIMON 27, 28 Y 44

Mecanismos básicos / Basic switches



Interrupor unipolar / Single-pole switch
XX00101-XX



Pulsador / Push button switch
XX00150-XX



Interrupor bipolar / Double pole switch
XX00133-XX



Conmutador / 2-way switch
XX00201-XX



Conmutador cruce / Intermediate switch
XX00251-XX

Mecanismos con piloto / Pilot switches



Interrupor unipolar / Single-pole switch
XX00102-XX



Interrupor bipolar / Double pole switch
XX00134-XX



Conmutador / 2-way switch
XX00202-XX



Interrupor unipolar / Single-pole switch
XX00104-XX



Pulsador / Push button switch
XX00160-XX



Conmutador / 2-way switch
XX2700204-XX



Conmutador cruce / Intermediate switch
XX2700254-XX