

DALI downlight white 735.31 WW Medium

REF. 73531330-683



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP20

DRIVER INCLUDED

Yes

LUMENS/W

3200 lm/33W

OPERATING TEMPERATURE RANGE (°C)

Max. temp.: 35°C

L70 (°C)

50,000 h

OPTICS

Medium

COLOR TEMPERATURE (K)

3000 K

L90 (°C)

50,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CONTROL

DALI

COLOR TYPE

WW

POWER (W)

33 W

CRI

80

LIGHTING EFFICIENCY (LM/W)

97 lm/W

SERVICE LIFE

50.000 h

LUMENS (LM)

3200 lm

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053285657

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053285657

PACKAGING VOLUME

9811125

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

135

PACKAGING GROSS WEIGHT

1.5

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

285

PACKAGING NET WEIGHT

1.2

UNITARY PACKAGING GROSS
WEIGHT

1.5

PACKAGING LENGTH

255

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

1.2