

Kit Flash 90 consisting of wireless charger 15W with Qi protocol white Simon 400

REF. 43390003-030



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a 15W Qi wireless charger for furniture installation. Includes all components for complete installation in white finish. Supplied with a power supply and power adapter terminated with a 3-pole Wieland® Gst18i male quick-connector with a safety anchor for easy connection and disconnection from the mains safely without interrupting the power supply. The kit is quick and easy to assemble, and connections are made via a male-female connection without the need for tools. Simply cut the die in the furniture where the product will be mounted and, once completed, connect it to the mains for operation.

FINISH

White

MATERIAL

Plastic

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

Yes

RJ45 CONNECTORS

No

CONNECTOR TYPE

Wireless

FORMAT

Wireless

IP RATING

IP43

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)

100/240 V~

RAL

9003

RECESS DIMENSION (MM)

ø80 mm

RJ45 ADAPTOR MODULE

No

SNAP-FIT RJ45 PLATES

No

SNAP-FIT TYPE

No

USB CHARACTERISTICS

QI Charging

USB CURRENT (A)

1,6 A

USB VOLTAGE (V~)

15 V~

VOLTAGE (V~)

240 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

No tools needed

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 | Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053406502

UNITARY PACKAGING GROSS WEIGHT

0.26

PACKAGING LENGTH

128

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.26

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

921600

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053406502

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.36

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

75

PACKAGING NET WEIGHT

0.26

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

96

PACKAGING WEIGHT UNIT

KGM