

Surface movement and brightness detector 7m white IP54

REF. 89102131-130



BASIC INFORMATION

DESCRIPTION

Surface PIR motion and light detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 7 m and the radial detection range is 3 m.

The light regulation range is 2 - 2000 lux and the timing range is 8 s - 35 min. The configuration of the detector is done through potentiometers.

The control output is On/Off and the maximum switchable power is 2000 W (350 W LED).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: -20 - 50 °C.

White finish, protection degree IP 54 and dimensions: Ø 115 x 50 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

MAXIMUM POWER (W)

2000

RAL

9010

IP RATING

IP54

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053341513

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.195

PRODUCT NET WEIGHT

0.12

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053341513

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

90

PACKAGING WIDTH

90

PACKAGING LENGTH

130

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1053000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.195

PACKAGING NET WEIGHT

0.12

PACKAGING WEIGHT UNIT

KGM