Industrial bell 819 120-200W CCT 90º

REF. **81942038-387**



BASIC INFORMATION

DESCRIPTION

Luminaire designed for industrial applications, suitable for high ceiling installations. High versatility thanks to its power and color temperature selector, which allows the luminaire to be adapted to each project with a single reference. Installation type: Suspended. Optics: 90º. Color temperature: 3000 / 4000 / 5000K. Power: 120 - 200W. Lumens: 36000lm. Efficiency: 180lm/w. IP protection rating: IP65. Power supply: 100-240 V. 50/60 Hz. Dimensions: 360 mm x 148 mm.

APPLICATION

General lighting for high ceilings,Industrial lighting

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IK CLASSIFICATION
09

IP RATING
IP65

OPERATING TEMPERATURE RANGE (°C)
-30...+45

POWER SUPPLY (V~)
100/240 V~

CONTROL
1-10 V

LIGHTING EFFICIENCY (LM/W)
180 lm/W

LUMENS (LM)
36000 lm

POWER (W)
120 - 200 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Suspension

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053440209

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
3.3

PRODUCT NET WEIGHT
2.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053440209

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
145

PACKAGING WIDTH
405

PACKAGING LENGTH
405

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
23783625

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3.3

PACKAGING NET WEIGHT
2.4

PACKAGING WEIGHT UNIT
KGM