

Sealing gasket circular for mechanism-holder unit IP66 Simon K45

REF. RKS004



BASIC INFORMATION

DESCRIPTION

Journeyman and protect your electrical panel for a possible input of water or dust with sealing gasket circular, for mechanism-holders of Simon K45 designed to give the most high security thanks to have measured IP66 as a guarantee of resistance. Manufactured with materials isolated in self-extinguishing thermoplastic free halogeneous, prevents the flame spread and toxicity by smoke in case of fire. It can reach temperatures of between -25 and 60 ° C, with a maximum temperature of 90 °C. Composed of rubber, to give a greater flexibility in the installation, with finishes in a black intense tone to maximize the integration of the whole set in any type of room. With a size of Ø 101 mm x 6 mm, this product is designed as a replacement of circular sealing gasket to house in the indoor of the unit mechanism-holders; this last is not included in the reference. With the range update, its equivalent for the new version is the KFS1003 reference.

FINISH

Black

PACKAGING CONTENTS

Circular sealing gasket for IP66 tray

ETIM CLASS

EC002420

MATERIAL

Rubber

REMARKS

Replacement for sealing gasket to order as substitution for the existing one (does not include mechanism-holder unit)

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

INSULATION RESISTANCE (V-MΩ)

>5 MOhm at 500 V

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 60° C

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90° C

IP RATING

IP66

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)

+650 °C (according to standard IEC 60670)

TYPE OF FASTENING

By unscrewing and extracting the mechanism-holder unit and substituting the old sealing gasket with the help of a tool for the new seal.

INSTALLATION DIRECTION

The sealing gasket is supplied with a pre-defined fitting position.

INSTALLATION TYPE

Product intended as a spare part for the circular sealing gasket which is housed inside the mechanism-holder unit (the article does not include the mechanism-holder unit).

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056398

PRODUCT NET WEIGHT

0.01

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

0.003

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436056398

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0.3

PACKAGING HEIGHT

20

PACKAGING NET WEIGHT

0.01

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.01

PACKAGING LENGTH

100