


Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 UTP aluminium Simon 500 Cima

REF. 50002085-033



BASIC INFORMATION

DESCRIPTION

In graphite finishes, the flat base plate of voice and data is available without dust cover and 1 element for 1 3M ® RJ45 that is part of the Simon 500 Cima series. Its measures are 50x50x11 mm, a thickness of 11 mmm and has been used components halogen-free in its manufacture. In this way, it guarantees no flame propagation in case of fire and a minimum toxicity in case of smoke. Finally, the plate includes clips for fastening in vertical and horizontal enclosures without the need of adapter. Is the most advanced solutions for your home thanks to our Simon 500 Cima series, one of the safest of our signature thanks to the use of the materials safest on the market, so that you the games and confident in our brand to make your home the best place for live.

FINISH

Aluminium

PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 UTP RJ45 connector and installation manual

ETIM CLASS

EC000018

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

AVAILABLE IN

Plate for 1 and 2 RJ45

RJ45 CONNECTION

With insertion tool

CONNECTOR CHARACTERISTICS

category 6 UTP

NUMBER OF CONNECTORS

1

RJ45 CONNECTORS

Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

DUST PROTECTION

Yes

DUST SHUTTER

Yes

FORMAT

RJ45

IP RATING

IP20

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

1

PLATE TYPE

Flat

RJ45 ADAPTOR MODULE

Included in voice and data plate

SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

VERSION

Single

INSTALLATION AND MAINTENANCE

REMOVAL OF CONNECTOR

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

REMOVAL OF THE PLATE

Only with tool

REGULATIONS

REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053098004

PACKAGING VOLUME

0.052

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

20

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS
WEIGHT

0.027

PACKAGING WIDTH

224

PACKAGING NET WEIGHT

0.54

PRODUCT NET WEIGHT

0.027

PACKAGING LENGTH

290

PACKAGING WEIGHT UNIT

KGM

