Push/pull module for Teleblock telescopic profiles with manual elevation Simon K45

REF. **KTLA3**



BASIC INFORMATION

DESCRIPTION

Push-pull module for telescopic profiles with manual elevation for Teleblock of the series Simon K45. It is manufactured in self-extinguishing halogen-free thermoplastic; guarantees no flame propagation in case of fire and the low toxicity in case of smoke and finished in black colour and its type is manual elevation. Its design follows the UNE-EN 60.670-23. It can withstand temperatures of -5 to 60 ° C The Simon K45 Teleblock solved the needs of connection number, adapting to any type of furniture and offers an automatic elevation that gives it a single of avant-garde technology, in addition to a design and originality to make this Teleblock on an image object of high level. Integration offers a perfect adaptation of the space in which it is located at the look hidden, if you want since it you can have the cables are sorted and hidden.

FINISH

Black

MATERIAL

Plastic

COMPATIBILITY

Teleblock with manual elevation from the Simon K45 range.

PACKAGING CONTENTS

Push-pull module and installation manual.

ETIM CLASS

EC002649

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
Without perforation or contournament with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 MOhm at 500 V

IP RATING
IP4X

KIT AVAILABILITY
No

LINKABLE
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

RAL
7021

INSTALLATION AND MAINTENANCE

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

TYPE OF FASTENING
By snap-fitting the module on to the Simon K45 Teleblock telescopic profile Note: this article is a replacement part and is supplied with the Simon K45 Teleblock telescopic profile.

REGULATIONS

REGULATIONS
Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60670-1:2005

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436051669

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
544320

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.045

PRODUCT NET WEIGHT
0.045

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436051669

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
72

PACKAGING WIDTH
72

PACKAGING LENGTH
105

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
544320

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.045

PACKAGING NET WEIGHT
0.045

PACKAGING WEIGHT UNIT
KGM