

Socket 16A 250V ~ with connection system 1click® Simon 100

REF. 10000458-039



BASIC INFORMATION

COMPATIBILITY

Frames Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

NOMINAL VOLTAGE (V~)

250 V~

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

CURRENT (A)

16 A

OPERATING TEMPERATURE

RANGE (°C)

0 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

IP RATING

IP20

STORAGE TEMPERATURE RANGE

(°C)

-25 - 75 °C

FORMAT

French

TYPE OF MECHANISM

Insertion

VERSION

Unique

MONOBLOCK

No

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

13

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

universal

INSTALLATION TYPE

Suitable for flush mounting

CLAW

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

1 click connection (1 click®)

REGULATIONS

REGULATIONS

EN 50581:2012 + IEC 60884-1 Ed 3.2

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS
WEIGHT
0.045

PRODUCT NET WEIGHT
0.046

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053142097

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
65

PACKAGING WIDTH
125

PACKAGING LENGTH
195

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
1584375

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.46

PACKAGING WEIGHT UNIT
KGM

