German socket outlet 16A 250V~ with hinged cover, safety device and screw terminal connection white Simon 27 Play

REF. **27490-35**



BASIC INFORMATION

DESCRIPTION

This Schuko socket outlet is perfect for sockets of elements of up to 16 A of current and 250 volts. It is part of the Simon 27 Play range, which stands out for its modernity. As well, the product has a built-in hinged cover and comes in white colour that will make you incorporate into everyday easily in any place where it is installed. The type of rocker operation of the socket is screwed and can be both surface or flush mounted, so that it provides versatility. It consists of two modules and measures 45 x 45 millimetres. The materials with which it is manufactured with the plug are of high quality and gives it great resistance. Therefore, consisting of metal components with halogen-free insulation and thermoplastic trim. Simon performs a commitment to clear the security of its products, but also for the security of users. In this sense, this plug, the covers include the child protection function.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with hinged cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
2,5 mm

NUMBER OF POSSIBLE ELEMENTS
1 element

FORMAT
Schuko

INDICATOR FUNCTION
No

CURRENT (A)
16 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM
Insertion

MONOBLOCK
No

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252345

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
1531530

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.054

PRODUCT NET WEIGHT
0.054

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053064962

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
55

PACKAGING WIDTH
91

PACKAGING LENGTH
306

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1201200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.54

PACKAGING NET WEIGHT
0.54

PACKAGING WEIGHT UNIT
KGM