

## POINT 56 spotlight Mini Rail 2700 K Spot On/Off White

REF. 92061011-200



### BASIC INFORMATION

#### BODY MATERIAL

Aluminium injection moulding

#### PACKAGING CONTENTS

1 Unit

#### APPLICATION

Domestic, Office, Retail, Hotel, Contract

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

90

### COLOR TYPE

WW

### IP RATING

IP20

### DIRECTIONAL

Yes

### LIGHTING EFFICIENCY (LM/W)

hasta 79 lm/W

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### DRIVER INCLUDED

Yes

### LUMENS (LM)

1010 lm

### POWER SUPPLY (V~)

220/240 V~

### ELECTRICAL CLASS

II

### NUMBER OF LUMINAIRES

1

### RAL

9016

### ENERGY EFFICIENCY

A+

### MACADAM STEPS

<3 Step MacAdam

### COLOR TEMPERATURE (K)

2700 K

### L70 (°C)

150000h at 25°C

### OPTICS

Spot 18°

### CONTROL

On/Off

### L90 (°C)

40000h at 25°C

### POWER (W)

14 W

### CHROMATICS CRI ICONS

CRI  
90

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Rail

## REGULATIONS

### EAC MARKED

No

### ECORRAE MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8436547052172

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.54

### PRODUCT NET WEIGHT

0.36

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8436547052172

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

83

### PACKAGING WIDTH

180

### PACKAGING LENGTH

298

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

4452120

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.4

### PACKAGING NET WEIGHT

0.36

### PACKAGING WEIGHT UNIT

KGM