

Custom button box 6 functions lighting, blinds and temperature with KNX coupling unit and slide control cold aluminium Simon 82 Sense

REF. 8400674-093



BASIC INFORMATION

FINISH

Matt aluminium

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Coupling unit, keypad, Slide Control, RJ12 cable and instructions

REMARKS

Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TYPE OF MECHANISM

Touch

NUMBER OF POSSIBLE ELEMENTS

2 elements

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

INDICATOR FUNCTION

Yes

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

INSTALLATION AND MAINTENANCE

BUS CABLE SECTION ADMITTED (MM)

From 0.5 to 0.8 mm

CABLE STRIPPING NECESSARY (MM)

8

INSTALLATION TYPE

Suitable for surface and flush mounting

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

CLAW

Optional

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016 + + + + + +

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053129517

PRODUCT NET WEIGHT

0.17

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

806880

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053129517

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.17

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

82

PACKAGING NET WEIGHT

0.17

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

82

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.17

PACKAGING LENGTH

120