

Floor trunking distribution baseboard with 2 punched holes (at 90°) and 2 pre-punched holes for DCS trunking stainless steel Simon Trunking

REF. KTA8229/8



BASIC INFORMATION

DESCRIPTION

Floor trunking distribution baseboard with 2 punched holes (90 °) and 2 pre-punched holes for DCS trunking stainless steel of the series Simon Trunking, its dimensions are 140 x 140 x 30 mm It is designed with 4 pre-punched holes for DCS trunking of 85 x 18 mm A great point in favour of this product is the distribution and branching of trunking, thanks to the adapter ALKA02 / 8, it is possible to the integration of K45 mini columns on the baseboard. Its cleaning is simple, as you only need to use use a soft and dry cloth and never use cloths or abrasive cleaners that contain chlorine in their formula, so that it does not get damaged and remains shiny. What makes this series of Simon Trunking, is that you can obtain all the benefits of a baseboard, but always taking into account the latest market trends, to always have the products most new and attractive that you can find. And also the can be set in any type of floor, and it will adapt both on a raised floor and one with a concrete floor.

FINISH

Metal

PACKAGING CONTENTS

Distribution plinth for floor trunking, protective foam, screws and installation manual

ETIM CLASS

EC002469

MATERIAL

Stainless steel

REMARKS

Designed with 4 pre-punched holes for DCS 85 x 18 mm trunking. See table in the event of requiring a different plinth configuration for the distribution of floor trunking. In addition to allowing the distribution and branching of trunking, it facilitates the integration of K45 mini columns on the plinth base, using the adaptor ref. ALKA02/8

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam in the base of the distribution plinth.

AVAILABLE IN

1 to 3 punched holes 130 x 18 mm and 1 to 4 pre-punched holes 85 x 18 mm (see selection table)

DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120° C

EARTHING RESISTANCE

< 0.05 ?

ELECTRICAL PROPERTIES

With electrical continuity

HEAT RESISTANCE (°C)

+850°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60° C

VERSION

2 punched holes 130 x 18 mm DCS trunking (at 90°) and 2 pre-punched holes 85 x 18 mm DCS trunking

INSTALLATION AND MAINTENANCE

TYPE OF FASTENING

Using supplied screws

INSTALLATION DIRECTION

Horizontal

INSTALLATION TYPE

Suitable for installing on any floor type, whether raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-2:2008

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436036604

PRODUCT NET WEIGHT

0.38

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1474200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436036604

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.372

UNITARY PACKAGING VOLUME

1474200

PACKAGING HEIGHT

63

PACKAGING NET WEIGHT

0.38

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.38

PACKAGING LENGTH

156