

## Flat voice and data plate with dust cover for 1 element with 1 RJ45 category 6 FTP graphite Simon 500 Cima

REF. 50003085-038



## BASIC INFORMATION

### DESCRIPTION

Voice and data flat plate with dust shutter, of the Simon 500 Cima series. It incorporates a single element, with an RJ45 connector, it is a product category 6 FTP, graphite grey finish. It has a module and is part of the individual version of the series. It is available, in addition, both for one and two connectors. It is manufactured with metallic components isolated from thermoplastic, which minimizes the flame spread in case of fire. Also, the voice and data plates of this series, does not contain halogens, guaranteeing the lower toxicity in case of smoke. With measures of 50 x 50 mm and 45,4 mm depth, the voice and data plates Simon 500 Cima, incorporate the clips necessary to be able to be fixed in any type of enclosure, both vertically and horizontally. It is, therefore, one of the most versatile and functional on the market and maintenance is simple.

### FINISH

Graphite

### PACKAGING CONTENTS

Flat voice and data plate with dust cover, category 6 FTP RJ45 connector and installation manual

### ETIM CLASS

EC000018

### COMPATIBILITY

Simon 500 Cima enclosures

### REMARKS

The plate is snap-fitted for mounting in vertical and horizontal enclosures without the need for an adaptor.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DUST PROTECTION

Yes

### PLATE TYPE

Flat

### CABLE SECTION ADMITTED (MM)

22-26 AWG wiring

### FORMAT

RJ45

### RAL

7021

### RJ45 CONNECTION

Without insertion tool

### IP RATING

IP20

### RJ45 ADAPTOR MODULE

Included in voice and data plate

### CONNECTOR CHARACTERISTICS

category 6 FTP

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### SNAP-FIT RJ45 PLATES

Keystone I, II, ATT®/Avaya®

### NUMBER OF CONNECTORS

1

### SNAP-FIT TYPE

Keystone I, II, ATT®/Avaya®

### RJ45 CONNECTORS

Included in voice and data plate

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### VERSION

Single

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### NUMBER OF MODULES

1

## INSTALLATION AND MAINTENANCE

### REMOVAL OF CONNECTOR

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

### INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

### INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

### REMOVAL OF THE PLATE

Only with tool

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018\*1

## LOGISTICS INFORMATION

### UNITARY PACKAGING HEIGHT

170

### UNITARY PACKAGING WIDTH

165

### UNITARY PACKAGING LENGTH

200

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

5610000

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.036

### PRODUCT NET WEIGHT

0.036

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053098028

### UNITS CONTAINED PACKAGING

20

### PACKAGING HEIGHT

112

### PACKAGING WIDTH

117

### PACKAGING LENGTH

269

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.052

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.72

### PACKAGING WEIGHT UNIT

KGM

