Voice and data flat plate without dust cover and 1 element with 1 RJ45 connector category 5e FTP white Simon K45

REF. **K095F/9**



BASIC INFORMATION

DESCRIPTION

The series Simon K45 to your collection incorporates the plate of voice and data plate without dust cover and 1 element with 1 RJ45 connector of category 5e FTP. With a few simple finishes white in colour, our piece is suitable for surface or flush mounting and has dimensions of 45x45 mm and a thickness of 8.5 mm, it also, is made of halogen-free metal components with self-extinguishing thermoplastic insulation to ensure that there are no fire, the flame spread and is very low toxicity in case of smoke. If you are looking for combining the voice and data plate in vertical enclosures (mini-columns, columns, Teleblock, channels, mechanism holders _ x0085 _), it would be necessary to use the 90º positioner to be able to guide the plate into a vertical position. The best solutions of workplace solutions are in our exclusive collection Simon K45, designed to meet to those who want to your home has all the news of the market. And all this is possible thanks to the commitment to our brand for the quality and innovation.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover category 5e FTP RJ45 connector and installation manual

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
22-24 AWG wiring

RJ45 CONNECTION
With insertion tool

CONNECTOR CHARACTERISTICS
Category 5e FTP

RJ45 CONNECTORS
Included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Keystone I, II, ATT®/Avaya®

SNAP-FIT TYPE
Keystone I, II, ATT®/Avaya®

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.03

PRODUCT NET WEIGHT
0.03

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436031968

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
65

PACKAGING WIDTH
155

PACKAGING LENGTH
210

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2115750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.42

PACKAGING NET WEIGHT
0.3

PACKAGING WEIGHT UNIT
KGM