

Two-pole MCB 10A 2 elements with trim plate for installation in floor boxes white Simon 500 Cima

REF. 50011075-030



BASIC INFORMATION

DESCRIPTION

In this category that includes all types of mechanisms and base plates for circuit protection, we find products that solve different needs. In this case, we present you this two-pole circuit breaker (10 Amps) of 2 elements with trim plate, suitable for installation in floor boxes, finished in white. This two-pole circuit breaker is another of the series that presents the successful Simon 500 Cima, dedicated to the workplace solutions in work stations. The dimensions of this product are 100 x 50 mm, being its depth of 81 mm As we know is the one miniature circuit breaker, a device that is capable for down and off the current electrical when values. In this case, the power of cutting is 6,000 A, being the trip Curve C Suitable exclusively in installations in raised floor and concrete floor. It is possible, in case of breakage, cover spare part of the request a specific adapter DIN rail. To do this, you should attend to the reference 50010076-039.

FINISH

White

PACKAGING CONTENTS

Two-pole circuit breaker 10A,
trim plate, adaptor for installing
it in Simon 500 Cima floor box
and installation manual

ETIM CLASS

EC000042

COMPATIBILITY

Floor boxes Simon 500 Cima

REMARKS

Possibility to order replacement DIN rail adaptor in case of breakage, with article no.50000076-039

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

Up to 25 mm

CURRENT (A)

10 A

NUMBER OF MODULES

2

BREAKING CAPACITY (A)

6000 A

IP RATING

IP4X

POWER SUPPLY (V~)

400 V~

NUMBER OF CONNECTIONS PER TERMINAL

1 connection per terminal

LINKABLE

Yes, using busbars 68002-31

RAL

9003

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE

MCB automatic switch

FORMAT

DIN

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

TRIP CURVE

C Curve

VERSION

Double

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

10

INSTALLATION DIRECTION

Vertical, corresponding with the direction of the mechanisms

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

INSTALLATION TYPE

Suitable only for installations in raised or concrete floor

NUMBER OF TERMINALS

4 (2 terminal connectors per pole)

REMOVAL OF THE MCB

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60898-1:2003 + EN 60898-1:2003 A1:2004 + EN 60898-1:2003 A11:2005 + EN 60898-1:2003 A12:2008 + EN 60898-1:2003 A13:2012

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053095966

PACKAGING VOLUME

3524976

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

5

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

112

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING GROSS WEIGHT

0.294

PACKAGING WIDTH

117

PACKAGING NET WEIGHT

1.47

PRODUCT NET WEIGHT

0.294

PACKAGING LENGTH

269

PACKAGING WEIGHT UNIT

KGM

