

## Upper trim for mini columns with 1 side grey Simon K45

REF. RALK009/8



### BASIC INFORMATION

#### DESCRIPTION

This product from the range Simon K45 is a upper trim mini specially designed for one-sided columns from the same series. Its grey colour allows it to integrate with columns of the same colour or graphite colour, but if you want to give modernity to the room you can also opt for creating contrasts, combining with other colours. Its measures are 70 x 60 millimetres and 3 millimetres of depth and is ideal to keep it as a replacement part in the event of loss of the original. Its manufacturing material is halogen-free thermoplastic that extends the service life of the product, which gives a high resistance. In this sense, in addition, as well as this halogen-free material is a commitment to safety as it does not flames in the case of fires and reduces the toxicity of smoke. Its installation is extremely simple, as well as its maintenance - it only requires wiping with a soft dry cloth without the need to use any type of chemical product.

#### FINISH

Grey

#### PACKAGING CONTENTS

Upper trim and fastening screws

#### MATERIAL

Plastic

#### ETIM CLASS

EC002980

#### REMARKS

Product envisaged as a replacement part, in the event of loss or substitution. It is supplied injected in grey plastic.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### AVAILABLE IN

1-sided, 2-sided (square and oval) and 4-sided

### DIELECTRIC STRENGTH

Without perforation or contournement with 2000 V at 50H during 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60° C

### EARTHING RESISTANCE

< 0.05 ?

### HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

### INSULATION RESISTANCE (V-MΩ)

5 MOhms at 500 V.

### IP RATING

IP4X

### KIT AVAILABILITY

No

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 a 120° C

### RAL

7035

### VERSION

1-sided

## INSTALLATION AND MAINTENANCE

### TYPE OF FASTENING

Using supplied screws

### INSTALLATION DIRECTION

Horizontal

## REGULATIONS

### REGULATIONS

UNE-EN 50.085-2-4-:2006

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8426436056503

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0.3

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.015

### PRODUCT NET WEIGHT

0.015

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8426436056503

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

20

### PACKAGING WIDTH

120

### PACKAGING LENGTH

80

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

0.192

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

0.015

### PACKAGING WEIGHT UNIT

KGM