Complete kit with 3 schuko socket outlets and plate for 2 RJ45 connectors black S400 Top

REF. **42403020-138**



BASIC INFORMATION

DESCRIPTION

Are you looking for a safe connection and functional? Thanks to the series Simon 400 Top the security is guaranteed since its covers and fastenings are manufactured in self-extinguishing thermoplastic that prevent the propagation of the flame in case of burning of electrical equipment, as they are made of halogen-free materials smoke generation will be low toxicity. A kit of desk top functional since it has 3 socket-outlets plug and a plate for 2 RJ45 connectors made of metal with a black finish, Simon offers a manual elevation system for this kit with 4 elements, whose dimensions are 205 x 120 x 80 millimetres. Suitable for 250 volts and a current of 16 amps. This kit has a trim cover painted steel and has great resistance, as its profile is made in anodised aluminium. A quality product, perfect for spaces that require von accessible and safe.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

IK CLASSIFICATION
07

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

OPERATING TEMPERATURE RANGE (°C)
-5...+60

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9005

NUMBER OF RJ45 WINDOWS
2

SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

SNAP-FIT TYPE
Keystone® I, II and Systimax®

NUMBER OF SOCKETS
3 sockets for standard current circuit

VERSION
4 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053195703

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.8

PRODUCT NET WEIGHT
0.8

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053195703

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
90

PACKAGING WIDTH
116

PACKAGING LENGTH
298

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3111120

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.8

PACKAGING WEIGHT UNIT
KGM