

Schuko socket outlet 16A 250V~ with safety device and quick terminal connection orange Simon K45

REF. K11/7



BASIC INFORMATION

DESCRIPTION

Se trata de una base de enchufe schuko 16 A 250V~ que cuenta con un dispositivo de seguridad y embornamiento rápido. Está incluido en la serie Simon K45, una colección que apuesta por la conectividad en cualquier espacio. Gracias a su sistema de embornamiento, la pieza puede instalarse en solo unos minutos. Asimismo, brinda la posibilidad de enlazar directamente las bases de enchufe, sin que sea necesario pelar ni trenzar los cables, mediante la referencia AC11. El enchufe tiene acabado en naranja y unas dimensiones de 45x45 mm. Fabricado en estricto cumplimiento con la normativa, contiene componentes metálicos con aislamiento en termoplástico autoextinguible y libre de halógenos. Estas especiales características garantizan que no se propague la llama en caso de incendio, así como la baja toxicidad. La pieza es apta para superficie y empotrar y tiene un fácil mantenimiento. Use una gamuza suave y seca para limpiarla, evitando los productos abrasivos.

FINISH

Orange

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-03X)

PACKAGING CONTENTS

Socket plug with trim cover and installation manual

ETIM CLASS

EC000125

REMARKS

Ability to link socket plugs directly without stripping or twisting cables, with article No. AC11

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INSULATION RESISTANCE (V-MΩ)

>5M? At 500 V

NUMBER OF MODULES

2 modules

CABLE SECTION ADMITTED (MM)

1,5 to 2,5 mm

CURRENT (A)

16 A

MONOBLOCK

No

NUMBER OF CONNECTIONS PER TERMINAL

2 connections per terminal

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

DIELECTRIC STRENGTH

Without perforation or
contournement with 2000 V at
50H during 1 minute

LINKABLE

Yes, using accessory AC11

RAL

2009

FORMAT

Schuko

MAINTENANCE

Clean with a soft, dry cloth. Do
not use abrasive cloths or
cleaning products that contain
chlorine.

NUMBER OF SOCKETS

1

VERSION

Single

HEAT RESISTANCE (°C)

+125°C (according rule IEC
60695-10-2)

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 a 60° C

INDICATOR FUNCTION

No

TYPE OF MECHANISM

Insertion

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

12

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45
and specific Simon 500 Cima
using adaptor ref.50012088-03X

REMOVAL OF THE SOCKET

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in
accordance with standard IEC
60695-10-2)

INSTALLATION DIRECTION

Vertical according to the
direction of the mechanisms

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

INSTALLATION TYPE

Suitable for surface and flush
mounting

NUMBER OF TERMINALS

2 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053263907

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

121251

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.058

PRODUCT NET WEIGHT

0.058

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053122921

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

49

PACKAGING WIDTH

101

PACKAGING LENGTH

245

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1212505

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.58

PACKAGING NET WEIGHT

0.58

PACKAGING WEIGHT UNIT

KGM