
IP66 Mechanism holder and security frame with italian P40 socket and RJ45 5e UTP

REF. **KFH135USEC/72**



BASIC INFORMATION

DESCRIPTION

Simon completely overhauls its range of waterproof floor boxes for indoor and outdoor environments. This is a device support frame with a security lock for environments that require restricted access, featuring an Italian P40 electrical base and a category 5e UTP RJ45 connector. In combination with its basin, it will allow installation in raised floors or pavements. The product design, combined with its stainless steel manufacturing, achieves a robust, solid, and secure installation as it withstands a water jet of 1 kg/cm^2 from any direction, achieving a protection rating of IP66 when the lid is closed. It also supports a maximum load of 1500 kg and has an IK08 impact resistance. It maintains an optimal cable bending radius for high-category voice and data connections. Our accessory for plug connection with a closed lid is available, so we can keep our connections active with an IP54 (see reference KFA1001), the possibility to level our box in case of having an irregular structure (see reference KFA1003), or the capability to chain multiple boxes together (see reference KFA1002).

FINISH

Steel

COMPATIBILITY

K45 Solutions

MATERIAL

Polycarbonate

ETIM CLASS

EC000024

REMARKS

To complete the installation of the product, it must be combined with a tray for the IP66 waterproof floor box.

TECHNICAL INFORMATION

FORMAT

Italian

IP RATING

IP66

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

IK CLASSIFICATION

08

KIT AVAILABILITY

Yes

CURRENT (A)

16 A

MAXIMUM LOAD (KG)

1500 Kg - Closed box | 250 Kg - Open box

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
1

EXTINGUISHING (ºC)
+650 ºC (according to standard IEC 60670)

REMOVAL OF THE FRAME
Only with tool

REMOVAL OF THE SOCKET
Only with tool

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 50173-1:2018 |EN 60670-23:2008 |EN IEC 63000:2018 |IEC 60884-1 Ed 3.2|CEI 23-50 V4

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053333068

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
0.384

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053333068

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
114

PACKAGING WIDTH
124

PACKAGING LENGTH
130

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1837680

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.462

PACKAGING NET WEIGHT
0.384

PACKAGING WEIGHT UNIT
KGM