Adjustable depth trap on 2 modules S for installation in a false floor graphite color Simon CIMA

REF. **SF210/14**



BASIC INFORMATION

FINISH
Graphite

MATERIAL
Various

COMPATIBILITY
With Simon Series S and Simon 25 / Simon K45 (using adapter) mechanisms.

ETIM CLASS
EC000024

TECHNICAL INFORMATION

NUMBER OF CLAMP-HOLDER HOLES
4

HEAT RESISTANCE (°C)
+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION
08

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

MAXIMUM LOAD (KG)
1400kg

RAL
7021

RECESS DIMENSION (MM)
170 x 155 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

NUMBER OF COVER OPENING POSITIONS
2

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8426436052567

UNITARY PACKAGING HEIGHT
100

UNITARY PACKAGING WIDTH
190

UNITARY PACKAGING LENGTH
175

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
3.325

UNITARY PACKAGING VOLUME UNIT
DMQ

UNITARY PACKAGING GROSS WEIGHT
1.15

PRODUCT NET WEIGHT
1.15

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436052567

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
100

PACKAGING WIDTH
190

PACKAGING LENGTH
175

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3.325

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
1.15

PACKAGING NET WEIGHT
1.15

PACKAGING WEIGHT UNIT
KGM