Aluminum profile Ofiblock Line with 6 elements and 4 rear wiring accesses black Simon K45

REF. **KFC236/14**



BASIC INFORMATION

FINISH
Black

MATERIAL
Metal,Plastic

COMPATIBILITY
Functions of the Simon K45 range and combinable with the Simon Electrical Wiring range.

ETIM CLASS
EC002759

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)
+125°C (according to standard IEC 60670)

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL
9003

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

EXTINGUISHING (°C)
+850 °C (according to standard IEC 60670)

INSTALLATION DIRECTION
Horizontal, Vertical

SECURING POSSIBILITIES
Its design allows it to be surface-mounted on the wall, on table-top furniture, under a desk, on a raised floor, a metal surface with magnet, or on a DIN rail using specific fastening accessories.

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053305690

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.332

PRODUCT NET WEIGHT
0.332

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053305690

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
59.5

PACKAGING WIDTH
317

PACKAGING LENGTH
54.5

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2.256

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.62

PACKAGING NET WEIGHT
0.332

PACKAGING WEIGHT UNIT
KGM