Neutral push-button switch 10A 250V~ for half element with fast terminal connection system white Simon 27 Play

REF. **27659-64**



BASIC INFORMATION

DESCRIPTION

Neutral push-button switch half element with quick terminal connection and finished in white colour of the Simon 27 Play series. This push-button switch with a voltage of 250V and an intensity of 10: 00 AM has has a rocker operation and is suitable for installation both in surface-mounted and recessed in places with a temperature located between 5 and 40ºC, although it can withstand extreme temperatures of between -25 to 50ºC. It is fully compatible with the frames of the series Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralizations and Simon 44 Aqua. There is the possibility of replacing the finish of the supplied rocker with 7 additional finishes that are available. It has 2 modules and supports a cable section of 1.5 to 2.5 mm, with a stripping of 11 mm It has been manufactured in accordance with the standards EN 60669-1: 1999 + A1: 2002 + A2: 2008 + EN 50581: 2012 and is made of metal components with halogen-free termpolytic fully halogen-free and the trim is made of thermoset material. To clean it, you have to do it with a soft, dry cloth without using never use abrasive cleaners or cloths with chlorine.

FINISH

White

MATERIAL

Thermoplastic

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000029

REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 5 additional finishes available.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

NUMBER OF POSSIBLE ELEMENTS

Half element

INDICATOR FUNCTION

No

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Pivoting

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (ºC)

5 - 40 ºC

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
11

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American, Small spaces and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Fast

REGULATIONS

REGULATIONS
Dir. 2014/35/UE LVD|Dir. 2011/65/UE RoHS + post. mod.|EN 60669-1:2018|EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252611

UNITARY PACKAGING HEIGHT
45.3

UNITARY PACKAGING WIDTH
36.7

UNITARY PACKAGING LENGTH
45.9

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0.076

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.024

PRODUCT NET WEIGHT
0.02

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053044759

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
48.5

PACKAGING WIDTH
85.7

PACKAGING LENGTH
224.5

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
0.933

PACKAGING VOLUME UNIT
DMQ

PACKAGING GROSS WEIGHT
0.47

PACKAGING NET WEIGHT
0.4

PACKAGING WEIGHT UNIT
KGM