

## Neutral push-button switch 10A 250V~ with fast terminal connection system ivory Simon 27 Play

REF. 27659-62



## BASIC INFORMATION

### DESCRIPTION

This neutral push-button switch for elements of up to 10A of intensity and 250 volts is part of the Simon 27 Play series. Simon products are looking for always substituting the function for which were designed, but at the same time, become decorative elements of the room where it is installed. For this reason, this product comes in a beautiful ivory colour that will give sophistication to the place where it is. The installation of the push-button switch is very simple and is carried out by means of recessed or surface-mounted. Its rocker operation is also simple and very interactive and user-friendly. The dimensions of the switch are 45 x 45 millimetres and requires quick terminal connection or for their start-up. The product is manufactured with metal components and the trim is made of thermoplastic, which gives the set of security is required, as it is able to work optimally low temperatures very high or very low. On the other hand, these materials ' s hardness to switch and thanks to this it can withstand external challenges with greater ease, as they can be knocks or scratches.

### FINISH

Ivory

### COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

### PACKAGING CONTENTS

Mechanism with rocker

### MATERIAL

Thermoplastic

### ETIM CLASS

EC000029

### REMARKS

Possibility of substituting the finish of the rocker supplied with a different one. 7 additional finishes available.

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### IP RATING

IP20

### NOMINAL VOLTAGE (V~)

250 V~

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### NUMBER OF POSSIBLE ELEMENTS

1 element

### VERSION

Single

### INDICATOR FUNCTION

No

### TYPE OF MECHANISM

Pivoting

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

11

### CLAW

Simon 27

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and  
Centralisations

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Suitable for surface and flush  
mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

## REGULATIONS

### REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053252604

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

1229865

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.032

### PRODUCT NET WEIGHT

0.032

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053044704

### UNITS CONTAINED PACKAGING

10

### PACKAGING HEIGHT

53

### PACKAGING WIDTH

105

### PACKAGING LENGTH

221

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1229865

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.315

### PACKAGING NET WEIGHT

0.32

### PACKAGING WEIGHT UNIT

KGM