

Downlight 725.22 Flush mount NW General IP44 White

REF. 72522930-984



BASIC INFORMATION

DESCRIPTION

Protected against the entry of external agents such as water or dust, thanks to the system IP44 included in the Downlight 725.22 Advance of Simon, makes it the best option to bring to the space of the maximum guarantee of security and lighting. Energy savings of its LED technology category B, is linked to its performance of 2300 lm for NW, and total luminaire consumption of 24 W and compatible with power supplies 100-240 Volts and 50-60 Hertz rate. It has a colour temperature of 3900 K obtaining a white tone neutral NW, and provides to each space a ambience visually comfortable thanks to its optics, also, for General photometric distribution. With control system, switching on ON-OFF, it has a service life of 30,000 hours at 25 ° C, which is not affected the quantity (QTY.) of times are power on or off luminaire. Also, it is designed for flush installation that, together with its finishes in a high colour White, guarantee total integration of the set in any space.

APPLICATION

General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

DRIVER INCLUDED

Yes

LUMENS (LM)

2300 lm

IP RATING

IP44

ELECTRICAL CLASS

Type 1

LUMENS/W

2300 lm/24W

OPERATING TEMPERATURE RANGE (°C)

-15 - 40 °C

INTEGRATED POWER SUPPLY

Yes

OPTICS

General

POWER SUPPLY (V~)

100/240 V~

L70 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

3900 K

LIGHT BEAM APERTURE ANGLE (°)

120°

POWER (W)

24 W

CONTROL

On/Off

COLOR TYPE

NW

SERVICE LIFE

30.000 h

CRI

80

LIGHTING EFFICIENCY (LM/W)

96 lm/W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface

INSTALLATION TYPE

Flush mount

MINIMUM INSTALLATION HEIGHT

107

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

REGULATIONS

WARRANTY

3 years 30,000 h

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.442

PRODUCT NET WEIGHT

1.442

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053116777

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

70

PACKAGING WIDTH

245

PACKAGING LENGTH

245

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0.042

PACKAGING VOLUME UNIT

HLT

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.442

PACKAGING WEIGHT UNIT

KGM