

19" ELECTROBLOCK with 6 Schuko sockets, with cable and RCD

REF. F1136/14



BASIC INFORMATION

DESCRIPTION

Manufactured with high-quality aluminum, the profile has been specially designed to withstand the high temperatures inside rack cabinets. The Electroblock's mounting flaps allow for multiple fixing positions within the rack, optimizing its internal space. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet. It is designed to power any electrical or electronic device housed inside the rack cabinet: hubs, switches, repeaters, routers, etc. It measures 1U in height (44.45 mm) to maximize space inside the cabinet and ensure compliance with IEC 60297 standards. The Electroblock is supplied pre-wired internally, with an instruction manual, and includes mounting brackets for the rack cabinet.

MATERIAL

Aluminium

COMPATIBILITY

19" Racks

ETIM CLASS

EC000330

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)	FORMAT
Up to 25 mm	DIN
BREAKING CAPACITY (A)	CURRENT (A)
10000 A (with upstream fuse)	25 A / 30 mA

LOGISTICS INFORMATION

UNITARY EAN CODE	PRODUCT NET WEIGHT	PACKAGING MEASUREMENT UNIT
8426436025684	1.11	MMT
UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT UNIT	PACKAGING VOLUME
0	KGM	2750000
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME UNIT
0	8426436025684	MMQ
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING GROSS WEIGHT
0	1	1.11
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING NET WEIGHT
2750000	55	1.11
UNITARY PACKAGING VOLUME UNIT	PACKAGING WIDTH	PACKAGING WEIGHT UNIT
MMQ	500	KGM
UNITARY PACKAGING GROSS WEIGHT	PACKAGING LENGTH	
1.11	100	